



WP402 is a series of premium, rugged, durable LED Wall Pack, which are perfect for outdoor perimeter and area lighting. With a die cast aluminum housing, a polycarbonate lens and a built in photocell, the WP402-26W-5K will stand up to many years of harsh environmental conditions. High-efficacy, long-life LEDs provide both energy and maintenance cost savings compared to traditional 75W MH / HID Wall Packs.

FEATURES

- * Standard in 5000k color temperatures 115 Lm/W, 2990 lumens
- * Long-life LEDs provide 50,000 hours of operation
- * Universal 120-277 AC voltage (50-60Hz) is standard
- * Power factor > 0.90
- * Working temperature : -40 F - 122 F
- * Dusk to dawn photocell
- * Total harmonic distortion < 20%
- * Color rendering index > 70
- * Die cast aluminum housing with dark bronze, powder coat paint
- * Polycarbonate clear lens
- * Easy installation in new construction or retrofit

ORDERING INFORMATION

PART #	Color Temp	Lumens	Lumen/watt	Wattage	Voltage
WP402-26W-50K-10-BR	5000K	2,990	115	26	AC 120-277V

WARRANTY & DETAILS

- * ETL Listed for "wet Location"
- * DLC Listed
- * IP 65 rated
- * Complies with RoHS (Restriction on Hazardous Substances) requirements
- * 5 year warranty on all electronics and housing

DIMENSIONS

